CITY OF OAKLAND

OFFICE OF THE CIT'S CLERA

AGENDA REPORT

FILED OFFICE OF THE CITY CLERA OAKLAHD

2007 NOV 29 PH 4: 15

NOV 29 Office of the City Administrator .

Deborah Edgerly Community and Economic Development Agency

From: Date:

December 4, 2007

Re:

Corrections to Pages 138 and 140 of the Ordinance Adopting Local Amendments to the 2007 Editions of the California Model Building Codes, California Code of Regulation (CCR), Title 24, Part 2 (Buildings), 3 (Electrical), 4 (Mechanical, and

5 (Plumbing), and Amending Oakland Municipal Code Chapter 15.04 to

Establish the 2007 Oakland Building Construction Code

At the Community and Economic Development Committee of November 27, 2007, staff noted two minor corrections (shown in underline text below) to the proposed ordinance referenced above:

In Article III, Part 2 – California Electrical Code:

15.04.705 In Article 210.11(c)(1) of the California Electrical Code, add the following new sentence.

"Each appliance fastened in place (fixed) including but not limited to dishwashers, garbage disposals, trash compactors, and microwave ovens, shall be supplied by a separate branch circuit rated for the appliance or load served."

and

15.04.765 In Article 695.13 of the California Electrical Code, add the following new sentence:

"Installations of fire pumps shall further conform with the requirements of the Oakland Fire Code as it pertains to Standard 20 of the National Fire Protection Association."

The corrected pages of the proposed ordinance are attached.

Respectfully submitted,

Development Director

Community and Economic Development Agency

APPROVED AND FORWARDED TO THE

ffice of the City Administrator

Item: City Council December 4, 2007

Article III

Part 2 - California Electrical Code

Non-Administrative (Technical) Amendments

15.04.700 In Article 210.8(a)(7) of the California Electrical Code, delete the words "wet bar".

15.04.705 In Article 210.11(c)(1) of the California Electrical Code, add the following new sentence.

"Each appliance fastened in place (fixed) including but not limited to dishwashers, garbage disposals, trash compactors, and microwave ovens, shall be supplied by a separate branch circuit rated for the appliance or load served."

15.04.710 In Article 210.12(B) of the California Electrical Code, add the following new sentence:

"Existing bedroom circuits shall have arc-fault protection as follows:

- (1) in an upgraded service panel of subpanel
- (2) where altered or extended. "

15.04.715 In Article 230.26 of the California Electrical Code, add the following new paragraph:

"The service point of attachment shall be installed on the building or structure wall facing the serving line. The service point of attachment on a periscope-type service shall be installed within eighteen (18) inches of the building or structure wall facing the serving line."

15.04.720 In Article 230.28 of the California Electrical Code, add the following new paragraphs:

"Whereas service conduit may be used as a mast to support service-drop conductors, it shall be rigid metal conduit or intermediate metal conduit not less than on and one-quarter (1.25) inch trade size. Aluminum rigid metal conduit shall be not smaller than two (2) inches trade size where used as a periscope.

Service conduit above a building or structure roof shall not extend more than thirty (30) inches beyond the last support without bracing. The outer or upper end of overhead service conduit shall extend horizontally not more than eighteen (18) inches beyond the point of support or fastening. Service conduit coupled above a structure or past the edge of same shall be braced or supported between the coupling and the point of attachment."

15.04.750 In Article 358.12 of the California Electrical Code, add the following new section:

Article 358.12(7) In concrete in direct contact with the earth.

15.04.755 In Article 410.16(c) of the California Electrical Code, add the following new paragraph:

"Fastening to the structure with no. 12 gage hangers and to the grid shall occur at diagonally opposite sides of 2x4 drop-in fixtures. Fixture installations shall further conform with the California Building Code Section 2504 and Standard 25-2, Section 25.213."

15.04.760 In Article 600.1 of the California Electrical Code, add the following new sentence:

"The provisions herein shall further include the requirements of the Oakland Sign Code."

15.04.765 In Article 695.13 of the California Electrical Code, add the following new sentence:

"Installations of fire pumps shall further conform with the requirements of the Oakland Fire Code as it pertains to Standard 20 of the National Fire Protection Association."

15.04.770 In Article 760.1 of the California Electrical Code, add the following new sentence:

"Installation of Fire Protection Signaling systems shall further conform with the requirements of the National Fire Protection Association recommended standards, the Oakland Building Construction Code and the Oakland Building Maintenance Code."

Article III

Part 3 - California Mechanical Code

Non-Administrative (Technical) Amendments

15.04.800 Adopt Appendix A - Standards of the California Mechanical Code in its entirety.

15.04.805 Adopt Appendix B, Chapters 10 – Steam and Hot Water Boilers, 12 - Hydronics, 14 – Process Piping, and 15 – Solar Systems in their entirety.

15.04.810 In Section 504.3.2.1 of the California Mechanical Code, at the following sentence after and separate from the Exception:

"Clothes dryers which are connected to a subduct exhaust system, as provided in the California Building Code, shall be equipped with an accessible secondary lint trap."

15.04.815 In Section 507.1.5 and Section 507.1.6 and Section 507.1.7 and section 516 of the California Mechanical Code, delete these sections in their entirety.